经纬纵横 ISURPASS TECHNOLOGY								
iSurpass Technology Smart Vending Machine Pursuing the Simplicity of Life http://www.isurpass.com.cn								
Tel: 86-18823765833 86-15874730192 0755-28761348								
Address: 42/F, Block C, Digital Innovation Center, No. 328, Min Tang Road, Minzhi Street, Longhua District, Shenzhen, China, Zip code#518131								
	Quotation 1386mm 936,,							
Product Pictures				105cm				
Product Name	18.5-inch touchscreen 42 doors lattice vending machine	55-inch touchscreen intelligent vending machine	21.5-inch touchscreen intelligent vending machine	21.5-inch touchscreen elevator vending machine	Mini vertical 18.5-inch touchscreen wall-mounted intelligent vending machine. Equipped with a portrait screen and a small window.	Mini horizontal 15.6-inch touchscreen desktop intelligent vending machine. Equipped with screen.		
Model No.	F1	T1	T4	\$4	M3	M4		
Product Characte ristics	Fast delivery speed, low failure rate and providing extra secure to commodity.	55 inch 4K super high definition large screen, providing better user interactive experience. Support customized refigeration, room temperature and heating requirements.	Eye-catching appearance. The sub- cabinet can be used to store the best-selling goods and reduce the frequency of transportation of it.Support customized refrigeration, room temperature and heating requirements.	 Large floor-to-ceiling glass window, better product display effect Pick up the goods in the middle of the right cabinet, the user does not need to bend over The XY axis addresses and picks up the goods, and the operator can arbitrarily adjust the height and width of the shelf within the specified range When the product is shipped, the drop is small in height, and it is suitable for selling blind boxes, daily necessities, beverages and snacks with a higher unit price. 	The body frame is light and thin, with its own wall hanging fixation base, which is suitable to be placed in the hotel, hospital, office corridor and other positions, which can make good use of the space.	Small machine, easy to handle and suitable for desktop scenario such as cashier		
Size Weight	W1532*H1928*D370mm About 220KG	1935*1155*920 (mm) About 270KG	1935*1252*876 (mm) About 320KG	1960 (H) *1386 (W) *955 (D) mm About 350KG	W560+H905+D260mm About 50KG	W810*H450*D260mm About 25KG		
	3.0 cold-rolled plate processing according to different functional	The body material is made of 0.4 mm double-layer Color Steel Plate, the inner liner is made of polyurethane foam, and the door, hopper, pallet and base are made of 1.0-3.0 cold- rolled plate according to different functional location.	The body material is made of 0.4 mm double-layer Color Steel Plate, the inner liner is made of polyurethane foam, and the door, hopper, pallet and base are made of 1.0-3.0 cold-rolled plate according to different functional location.	The body material is made of 0.4 mm double-layer Color Steel Plate, the inner liner is made of polyurethane foam, and the door, hopper, pallet and base are made of 1.0-3.0 cold-rolled plate according to different functional location.	According to the function location, the machine body material, door, hopper, tray, base and so on adopt 1.0-3.0 cold-rolled plate processing.	The body material, door, bucket, tray and base are processed with 1.0-3.0 cold-rolled plate according to different functional location.		
Display	18.5 inch, BOE, Resolution: 1366 * 768 pixels, Brightness 350 CD / m2	55 inch, LG, 4K Resolution: 1920 +1080 pixels, Brightness 350cd / m2	21.5 inch, LG / AUO Resolution: 1920 + 1080 pixels, Brightness 350 cd / m2	21.5-inch,LG/AU/Innolux Resolution: 1920+1080 pixels, Brightnes 350 cd/m2	18.5 inch, BOE, Resolution: 1366 + 768 pixels, Brightness 350 CD / m2	15.6 inch, BOE, Resolution: 1920 * 1080 pixels, Brightness 250 CD / m2		
Touch Screen	18.5 inch capacitance multi touch, Touch response speed: < 15ms	55 inch infrared 10 point touch, touch response speed: < 15ms	21.5 inch capacitance multi touch, Touch response speed: < 15ms	21.5 inch capacitance multi touch Touch response speed: <15ms	18.5 inch capacitance multi touch, Touch response speed: < 15ms	15.6 inch capacitance multi touch, Touch response speed: < 15ms		
Main Broad	Main Board: RK3288 2GB Ram + 8GB Rom	Main Board: RK3288 2GB Ram + 8GB Rom	Main Board: RK3288 2GB Ram + 8GB Rom	RK3288 2GB Ram + 8GB Rom	Main Board: RK3288 2GB Ram + 8GB Rom	Main Board: RK3288 2GB Ram + 8GB Rom		
Single- Chip Microco mputer	Control unlocking and closing the lock Built in external extension 4G module Support the brightness adjustment of cabinet lamp Support external communication control	Support 8+10 freight lanes Support the brightness adjustment of cabinet lamp Support to expand the sub cabinet	Support 8 + 10 freight lanes Support the brightness adjustment of cabinet lamp Support to expand the sub cabinet	Support 80 cargo lanes Support sound and light control Support multi-model feedback sensor control Support positioning by lifting	Support 8 + 10 lane arrangement. Support brightness adjustment of cabinet lamp. Support expand of sub-cabinet.	Support 8 • 10 lane arrangement. Support brightness adjustment of cabinet lamp. Support expand of sub-cabinet.		
Menu Operatio n	Capacitor touch screen menu purchase	Infrared touch screen menu purchase	Capacitor touch screen menu purchase	Capacitor touch screen menu purchase (Android system)	Capacitor touch screen menu purchase	Capacitor touch screen menu purchase		
Payment Method	Credit Card_NayaX / QR code	Credit Card_NayaX / QR code	Credit Card_NayaX / QR code	Credit Card_NayaX / QR code	Credit Card_NayaX / QR code	Credit Card_NayaX / QR code		
Network Require ments	WiFi / 4G	WiFi / 4G	WiFi / 4G	WiFi / 4G	WiFi / 4G	WiFi / 4G		
Capacity	42 items	Standard 6 lines, 9 columns, 54 freight lanes(adjustable, customizable)	Standard 6 lines, 9 columns, 54 freight lanes(adjustable, customizable)	Standard 6 lines, 9 columns, 54 freight lanes(adjustable, customizable)	Standard 4 lines, 2 columns,total 8 workable lanes (adjustable, customizable)	Standard 2 lines, 3 columns,total 6 workable lanes (adjustable, customizable)		
Columns Numbers	Small: 139+133+300mm, 16 columns Medium: 186+177+300mm, 18 columns Large: 280+170+300mm, 8 columns	270-648(depending on the size of the product)	270-648(depending on the size of the product)	6 layers-9 columns, 54 SKUS total (adjustable and customizable)	40-96(depending on the size of the product)	30-72(depending on the size of the product)		
Cooling System	Room temperature	High-efficiency and energy-saving compressor, support timing switch, freely adjust temperature.	High-efficiency and energy-saving compressor, support timing switch, freely adjust temperature.	High-efficiency and energy-saving compressor Support timing switch, freely adjust temperature	40-96(depending on the size of the product)	30-72(depending on the size of the product)		
Power	About 150W	About 600W when refrigerating and about 150W when not refrigerating	About 600W when refrigerating and about 150W when not refrigerating	About 700W when refrigerating and about 250W when not refrigerating	About 80W	About 75W		
Voltage	AC220 V / 50 Hz, protection against electric shock	AC220 V / 50 Hz, protection against electric shock	AC220 V / 50 Hz, protection against electric shock	AC220 V / 50 Hz, protection against electric shock	AC220 V / 50 Hz, protection against electric shock	AC220 V / 50 Hz, protection against electric shock		

Remark	 Price based on EXW (shipping cost, tax & payment system not included) Price not including wooden box packing. Customers can choose payment systems according to their needs, Credit cards and QR code are available, and the prices are as follows: Credit card: 450USD - (Nayax) Q.QR code: Please consult for details A Subset of the Place consult for details
	4).Customized Skin Wrapping Design: 90USD (Optional)